simpleaccess ™

Secure Access Control. Simplified.

Nickel Finish

700 SERIES
Wi-Fi Enabled Smart Lock

This Wi-Fi enabled smart lock can be connected directly to the internet without a hub. The 700 series locks is designed for moderate commercial traffic applications.

Key Features

- Designed to be easy to install, connect, manage, and use
- Built-in Wi-Fi for standard connectivity with no gateway or hub required
- Remote control and monitoring from anywhere using your smartphone or laptop
- Supports passage mode, auto-lock mode, and passage schedules
- Retains all programming and data during a power outage or internet interruption
- Low battery warning indicator
- Store up to 40 weekly access schedules (e.g., M-F, 9-5)
- Receive alerts and notifications for user entry or unexpected issues
- Auto lockout functionality after 5 incorrect code attempts
- Set temporary codes for guests and visitor management
- Includes 2 override keys
- Works with wired and wireless access control solutions

Silver Finish

700 **SERIES** Wireless Locks

710
- PIN Codes
- Remotely Lock/Unlock

720C
- PIN Codes
- Remotely Lock/Unlock
- Access Control Cards & FOBs

Product Specifications

Environment:	For normal interior and exterior use
Exterior Dimensions:	7-5/8 (H) x 2-3/4 (W) x 2-3/4 (D) in.
Interior Dimensions:	7-5/8 (H) x 2-3/4 (W) x 2-3/4 (D) in.
Backset:	2-3/8 in. (60mm) or 2-3/4 in. (70mm)
Locking Device:	Tubular latch included (mortise latch available)
Construction:	Zinc alloy, suitable for indoor & outdoor use
Operating Temperature:	-31°F (-35°C) to 151°F (66°C)
Thickness:	1-3/8 - 2-3/8 in. (35mm - 60mm)
Door Handing:	Non-handed, field reversible
Batteries:	4 AA (not included)
Keyway:	6-pin Schlage C (SF IC core available)
Code Length:	4 - 10 digits
Code Capacity:	Up to 3,500
Communication:	Single band 2.4GHz Wi-Fi (IEEE 802.11b/g/n) with WPA/WPA2
Standards:	Tested to Grade 2 A NSI A156.2/A156.25, UL/ULC fire rating 3 hours (when fitted w/ US fire kit)

simple access ™