

Card Model ValuProx 125kHz 26-bit ISO Proximity Cards
Part Numbers VP-26Prox, VP-26ProxComp

Programming (Choose)
L - Programmed, Low Frequency (125kHz). Specify programming information below.

Front Packaging
G - Plain White PVC w/ Gloss Finish

Back Packaging¹
G - Plain White PVC w/ Gloss Finish

Card Numbering^{2,3} (Choose)
 M - Sequential Matching Internal/External (Inkjetted)
 N - No External Card Numbering
 S - Sequential Internal/Sequential Non-Matching External (Inkjetted)

Slot Punch⁴ (Choose)
 N - No Slot Punch (Printed location of vertical and horizontal slot punch will remain)
 V - Vertical Slot Punch (Printed location of horizontal slot punch will remain)
 H - Horizontal Slot Punch (Printed location of vertical slot punch will remain)



Final Part Number LGG (Refer to Options Above)

26-bit, 125kHz Card Programming Information

Facility Code

Internal Card Start Number

External Card Start Number (if non-matching)

1. Cards will have a small ValuProx logo ValuProx, and card number printed in the lower left-hand corner, and slot punch guides printed on the back of the card.
2. The external card number is placed in the bottom right-hand corner on the back of the card.
3. Programmed as a sequential 12-digit number.
4. Cards are provided with an optional slot punch at no additional charge. Some card printers cannot accomodate pre-slot punched cards. Consult with your Account Manager prior to ordering.